

VL audio S04N25 Speaker cable

Item	4*2.5mm2 Speaker cable	Spec	$\Phi 11.5\text{mm}[(140/0.15\text{BC}*3.5\text{mm})*4\text{C}]$
Conductor	Size	NO/mm	140/0.15BC
	Twist pitch(DIR)	mm	/
Insulation	Material	/	75P PVC
	Color	/	Red/Black/White/Yellow
	Ave.thick	mm	0.85
	Min. thick	mm	0.82
	OD	mm	3.5 ± 0.05
Filler	Material	mm	/
	OD	mm	/
Twisting	Twist	mm	$S P=155\pm 5\text{mm}$
	Total twist OD	mm	$8.4\pm 0.5\text{mm}$
Shielding	Overlapping	mm	/
	Spiral	/	/
Outer jacket	Material	/	Environmental PVC
	Color	/	70P High flexible (MATTE) Black
	Ave.thick	mm	1.5
	Min. thick	mm	1.4
	OD	mm	$\Phi 11.5\pm 0.15\text{mm}$
Electrical Data	Conductor-Conductor capacitance	PF/Km	<145.3
	Conductor-Shielding capacitance	PF/Km	/
	Conductor resistance (20°C)	Ω /Km	6.88
Marking			V-LINE S04N25 4*2.5mm2 PROFESSIONAL HIGH QUALITY SPEAKER CABLE BY VLAUDIO
Packaging		/	100M/ROLL
<p>Profile:</p> 			