


### VL audio S04N40 Speaker cable

Item	4*4.0mm2 Speaker cable	Spec	$\Phi$ 14.3mm(226/0.15BC*4.2mm)*4C
Conductor	Size	NO/mm	226/0.15BC
	Twist pitch(DIR)	mm	/
Insulation	Material	/	75P PVC
	Color	/	Red/Black/White/Yellow
	Ave.thick	mm	0.97
	Min. thick	mm	0.92
	OD	mm	4.2±0.05
Filler	Material	mm	/
	OD	mm	/
Twisting	Twist	mm	S P=155 ± 5mm
	Total twist OD	mm	10.2 ± 0.5mm
Shielding	Overlapping	mm	/
	Spiral	/	/
Outer jacket	Material	/	Environmental PVC
	Color	/	70P High flexible ( MATTE ) Black
	Ave.thick	mm	2.08
	Min. thick	mm	2.05
	OD	mm	$\Phi$ 14.3 ± 0.15mm
Electrical Data	Conductor-Conductor capacitance	PF/Km	<236.7
	Conductor-Shielding capacitance	PF/Km	/
	Conductor resistance (20°C)	$\Omega$ /Km	4.3
Marking			V-LINE S04N40 4*4.0mm2 PROFESSIONAL HIGH QUALITY SPEAKER CABLE BY VLAUDIO
Packaging		/	100M/ROLL
<p>Profile:</p>  <p style="margin-left: 200px;">             Conductor: 226/0.15BC              Insulation: OD4.2 ± 0.05              Outer jacket: <math>\Phi</math> 14.3 ± 0.15         </p>			