



CNI-62

6-INCH 2WAY COAXIAL CEILING LOUDSPEAKER 70V/100V 30W



SOUNDVISION™

CNI-62 6-inch 2-Way Coaxial ceiling loudspeaker 30Watts is ideal for indoor applications requiring high-quality sound. designed for a wide range of commercial line transformers with multiple for use in 70V / 100V Taps at 70V : 30W/15W/7.5W/3.75W/1.88W , 30W@8Ω
100V: 30W/15W/7.5W/3.75W , 30W@8Ω

CNI-62 Applications designed suitable, such as hotels, restaurants, bars, lounges, training and conference rooms, or shopping centers.

FEATURE

- 6-inch 2-Way Coaxial ceiling loudspeaker for installation
- Elegant design ceiling loudspeaker "Borderless"
- Magnetic grille to make installation easier.
- High-quality sound.
- Frequency response 70Hz~18KHz
- Transformer taps 70V, 100V

SPECIFICATIONS

Speaker type	Coaxial ceiling loudspeaker. Two-Way
Rated power	30W
Line voltage	70V / 100V
Transformer taps	70V : 30W/15W/7.5W/3.75W/1.88W , 30W@8Ω 100V: 30W/15W/7.5W/3.75W , 30W@8Ω
Frequency response	70Hz ~ 18kHz (-3dB)
Sensitivity 1W/1 m	90 ±3dB
Maximum SPL/1m (calc)	110dB
Coverage (Nominal -6 dB) H	160° (±5°)
Coverage (Nominal -6 dB) V	150° (±5°)
Driver LF Transducer	1 x 6-inch (Woven Kevlar Cone)
Driver HF Transducer	1 x 1-inch (Silk dome)
Nominal impedance (Passive)	8Ω
Operating temperature	-20 °C to +55 °C
Connections	Phoenix connector
Indoor applications	Yes
Color	White
Cabinet material	ABS enclosure
Front grille	Metal grille
Dimensions hole for mounting	Φ 205mm
Dimensions	Φ 235 x H 101mm (without bracket)
Weight	1.6 Kg