


LA210

Applications


- Touring performance
- Theatre and multi-function hall
- Church

Feature


- Small and medium sized full range line array speaker
- Presettable angle on the ground adjustable angle with manual hoister in the air
- Small enclosure, High SPL and volume ratio



Frequency response



Impedance




Phase response

Technical specification


- **FREQUENCY RESPONSE:** 50 Hz-16 kHz(±3 dB) 40 Hz-18 kHz(-10 dB)
- **NOMINAL COVERAGE^(-6dB):** 100° (H)
- **SENSITIVITY(@1w/1m)** HF/LF: 112 dB SPL / 96 dB SPL
- **POWER RATING(AES):** HF/LF: 120W/800W(AES)
- **NOMINAL IMPEDANCE** HF/LF: 16/16 ohm
- **MAXIMUM SPL:** HF: 138 dB SPL peak
LF: 131 dB SPL peak
- **DRIVERS:** LF 2x10" woofer (75mm voice coil)
HF 1x3" compression driver

Physical data


- **DIMENSIONS(HxWxD):** 303.4 x 730 x 464.5mm
- **WEIGHT:** 35 kg / 77 lbs
- **CONNECTORS:** 2 x NL4 connectors
- **SPEAKER CABLES** 1+1...Full range, 2+2... N/C
- **MATERIALS:** 15mm 18mm Baltic birch plywood
- **FINISH:** Black Polyurea paintings
- **GRILLE:** Black epoxy mesh grille with acoustically reticulated cloth
- **RIGGING:** 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 degree adjustable



Front



Side



Top