



Deliver More for Less with the World's Smallest and Lightest 16,000 lm 3-Chip DLP™ 4K Projector

PT-RQ18K

Deliver More for Less with the World's Smallest and Lightest 16,000 lm 3-Chip DLP™ 4K Projector

Key Features

Compact Form-Factor Streamlines Workflow

Create an Engaging Visual Experience

Maintenance-free for Peace of Mind

3-Chip DLP™ 4K Laser Projector with Quad Pixel Drive

16,000 Lumen Brightness



PT-RQ18K

<https://eu.connect.panasonic.com/gb/en/products/projectors/pt-rq18k>

| | |
|---|---|
| Light Output*1 *2 | 16,000 lm / 16,800 lm(Center) *3 |
| Power consumption Maximum power consumption | AC 200 V-AC 240 V : 1,190 W(1,220 VA) |
| | AC 100 V-AC 120 V : 1,080 W(1,090 VA) |
| Power consumption On-mode power consumption (Operating mode)[Normal] | 1,030 W |
| Power consumption On-mode power consumption (Operating mode)[Eco] | 820 W |
| Power consumption On-mode power consumption (Operating mode)[Quiet] | 810 W |
| Operation Noise*2 | 43 dB (NORMAL/ECO), 40 dB (QUIET) |
| Projector type | 3-Chip DLP™ projector |
| DLP™ chip Panel size (mm) | 20.3 mm (0.8 in) diagonal (16:10 aspect ratio) |
| DLP™ chip Panel size (inch) | 20.3 mm (0.8 in) diagonal (16:10 aspect ratio) |
| DLP™ chip Number of Pixels | 2,304,000 (1920 x 1200 pixels) x 3 |
| Light Source | Laser diode |
| Resolution | 4K (3840 x 2400 pixels) (Quad Pixel Drive: ON) |
| Contrast Ratio*2 | 25,000:1 (Full On/Full Off, Dynamic Contrast [3]) |
| Screen size (diagonal) (mm) | 1.78-25.40 m (70-1000 in), 1.78-15.24 m (70-600 in) with ET-D75LE8/ ET-D3LET80, 3.05-15.24 m (120-600 in) with ET-D75LE95, 5.08-15.24 m (200-600 in) with ET-D3LEU100/D3LEW200 |
| Screen size (diagonal) (inch) | 1.78-25.40 m (70-1000 in), 1.78-15.24 m (70-600 in) with ET-D75LE8/ ET-D3LET80, 3.05-15.24 m (120-600 in) with ET-D75LE95, 5.08-15.24 m (200-600 in) with ET-D3LEU100/D3LEW200 |
| Center-to-corner zone ratio*2 | 90 % |
| Lens | Optional (no lens included with this model) |
| Lens shift Vertical(From the origin point of the lens mounter) | ±66 % (±52 % with ET-D75LE6/ET-D3LEW60, +71 % / +93 % with ET-D75LE95, ±66 % with ET-D3LEU100, ±57 % with ET-D3LEW200) (powered) |
| Keystone Correction Range | Vertical: ±45 ° (± 40 ° with ET-D75LE10/ET-D3LEW10/ET-D75LE20/ET-D3LES20, ±28 ° with ET-D75LE6/ET-D3LEW60, ±22 ° with ET-D3LEW50, ±15 ° with ET-D3LEW200, ±8 ° with ET-D3LEU100, +5 ° with ET-D75LE95), Horizontal: ±40 ° (±15 ° with ET-D3LEW50/ET-D75LE6/ET-D3LEW60, ±5 ° with ET-D3LEU100/ET-D3LEW200, 0 ° with ET-D75LE95) When [VERTICAL KEYSTONE] and [HORIZONTAL KEYSTONE] are used simultaneously, correction cannot be made exceeding a total of 55 °. |
| Terminals HDMI In | HDMI x 2 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input**5) |
| Terminals Multi Projector Sync In | BNC x 1 |
| Terminals Multi Projector Sync Out | BNC x 1 |
| Terminals MULTI PROJECTOR SYNC IN / 3D SYNC 1 IN/OUT(dual purpose) | - |
| Terminals MULTI PROJECTOR SYNC OUT / 3D SYNC 2 OUT(dual purpose) | - |
| Terminals Serial In | D-sub 9-pin (female) x 1 for external control (RS-232C compliant) |
| Terminals Serial Out | D-sub 9-pin (male) x 1 for link control (RS-232C compliant) |
| Terminals REMOTE 1 IN | M3 stereo mini-jack x 1 for wired remote control |
| Terminals REMOTE 1 OUT | M3 stereo mini-jack x 1 for link control (for wired remote control) |
| Terminals Remote 2 In | D-sub 9-pin (female) x 1 for external control (parallel) |
| Terminals LAN | RJ-45 x 1 for network connection, PjLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible |
| Terminals USB | USB connector (Type A) x 1 for optional AJ-WM50 Series Wireless Module/USB memory |
| Terminals DC Out | USB Type A x 1 (for power supply, DC 5 V, 2 A) |
| Terminals Expansion Slot | Open slot for for function boards, Intel® SDM compatible |
| Power Supply | AC 100 V-120 V / AC 200 V-240 V, 50 Hz/60 Hz (The maximum value of light output is limited to 15,000 lm or less when using the projector with AC 100 V to AC 120 V. Other limitations apply*6 .) |
| Applicable software/application | Logo Transfer Software, Multi Monitoring & Control Software, Projector Network Setup Software, Early Warning Software, Geometry Manager Pro, Smart Projector Control for iOS/Android™ |

| | |
|---|---|
| Note | <p>*1 This is the value when the Zoom Lens (Model No.: ET-D3LES20) is used with power supply voltage of AC 200 V to AC 240 V. The value varies depending on the lens.</p> <p>*2 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards.</p> <p>*3 Average light-output value of all shipped products measured at center of screen in NORMAL Mode.</p> <p>*4 Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast contents, NORMAL Mode, Dynamic Contrast [3], under conditions with 35 °C (95 °F), 700 m (2,297 ft) above sea level, and 0.15 mg/m³ of particulate matter. Estimated time until light output decreases to 50 % will vary depending on environment.</p> <p>*5 4K signals are converted to WUXGA (1920 x 1200 pixels) only for the PT-RZ24K and PT-RZ17K.</p> <p>*6 Maximum value of light output is further decreased in the following cases: when a function board is installed in the slot, when the light source is deteriorating from use, or when there is dust on the optical parts.</p> <p>*7 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft).</p> <p>*8 Average value. May differ depending on the actual unit.</p> <p>*9 When optional AJ-WM50 Series wireless module is attached, operating temperature range becomes 0–40 °C (32–104 °F). The operating environment temperature should be between 0 °C (32 °F) and 40 °C (104 °F) if the projector is used at an altitude between 1,400 m (4,593 ft) and 4,200 m (13,780 ft).</p> |
| Terminals DisplayPort | DisplayPort™ x 1 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input**5) |
| Dimensions (W x H x D) | Approx. 550 x 220 x 570 mm (21 5/8" x 8 11/16" x 22 7/16") (not including protruding parts) |
| Operating Environment | Operating temperature: 0–45 °C (32–113 °F*9), operating humidity: 10–80 % (no condensation) |
| Time until light output declines to 50 %*4 | 20,000 hours (NORMAL/QUIET), 24,000 hours (ECO) |
| Lens shift Horizontal(From the origin point of the lens mounter) | ±24 % (±18 % with ET-D75LE6/ET-D3LEW60, ±14 % with ET-D75LE95, -25 % / +30 % with ET-D3LEU100, ±18 % with ET-D3LEW200) (powered) |
| Weight*8 | Approx. 35 kg (77.2 lbs) |